

STANDARD FEATURES

- Compact Design
- Pre-assembled
- Easy Installation
- Simple & Reliable Operation
- Wide range of flow rates and materials of construction
- PVC Piping

OPTIONS

- Carbon Steel or Stainless Steel Piping
- Motor Starter
- Variable Frequency Drives



Centrifugal Pump Skid

GENERAL

The pumps can be controlled by either storage tank level sensor or the main control panel. Our control engineers can work with you to find the most appropriate standard panel to fit your needs. The pumps chosen are used worldwide and are highly rated for their reliability. The piping can be chosen to be either stainless steel, carbon steel or schedule 80 PVC. All piping is hydrostatically tested at the factory. There are several options and NEMA Ratings for the electrical panel. All skid wiring is completed and tested before shipment.

APPLICATIONS

- Tank Forwarding Pumps
- Water Pressure Booster Pumps
- Plant Water Loop Pumps
- Service Water Pumps

Centrifugal Pump Skid

Model Number	Pump Model #	MAX FLOW GPM	Available Pipe Material	Pump Suction Pipe	Pump Discharge Pipe	Shipping weight (LBS)	Dimensions (Inches)		
				INCHES	INCHES		H	W	D
CP2-10	CRN1	5 to 10	SS / CS / PVC	1"	1"	350	66	50	40
CP2-35	CRN5	16 to 35	SS / CS / PVC	2"	1-1/2"	400	66	52	40
CP2-55	CRN10	35 to 55	SS / CS / PVC	2"	2"	480	66	52	40
CP2-90	CRN1	55 to 90	SS / CS / PVC	3"	2"	550	66	78	45
CP2-120	CRN20	90 to 120	SS / CS / PVC	3"	3"	580	66	78	45
CP2-160	CRN32	120 to 160	SS / CS / PVC	4"	3"	700	66	78	45
CP2-280	CRN45	160 to 280	SS / CS / PVC	6"	4"	1150	66	94	60
CP2-500	CRN90	280 to 500	SS / CS / PVC	8"	6"	1250	66	98	60

