

STANDARD FEATURES

- Skid mounted unit
- Self standing chemical solution tank
- PVC piping
- Vertical inline cleaning pump
- 10 micron cartridge filter with stainless steel housing
- Local flow meter

OPTIONS

- Electric heater for chemical tank with temperature controller
- Flexible hoses for cleaning connection
- Wheel mounted skids for smaller units



Membrane Clean-in-Place Skid (CIP)

GENERAL

The CIP unit is designed for manual operation through a local control box on the skid. A chemical storage tank is mounted on its own stand and connected to the CIP skid with either hard PVC piping or quick disconnect fittings and flexible hoses. This gives the unit the ability to be mounted in a permanent location or totally portable if desired. The piping is schedule 80 PVC that is hydrostatically tested at the factory. The electrical enclosure is NEMA 12. All skid wiring is completed and tested before shipment.

APPLICATIONS

- Membrane Cleaning
- Descaling

Membrane Clean-in-Place Skid Matrix

Model Number	Pump Model #	MAX FLOW	Pipe Material	Pump Suction Pipe	Pump Discharge Pipe	Reqd Tank Capacity Gal	Tank Inlet Size	Tank Outlet	Overflow	Drain	Shipping weight	Dimensions (Inches)		
		GPM		INCHES	INCHES	GALLONS	INCHES	INCHES	INCHES	INCHES	(LBS)	H	W	D
RC-110	CRN15-3	60 - 110	PVC	4"	2"	350	2"	4"	3"	2"	850	80	103	110
RC-160	CRN32-2-2	110 - 160	PVC	4"	3"	400	2"	4"	3"	2"	960	92	105	115
RC-190	CRN32-2	160 - 190	PVC	6"	4"	500	2"	6"	3"	2"	1020	92	108	116
RC-350	CRN62-2-2	190 - 350	PVC	6"	4"	1000	2"	6"	3"	2"	1200	100	108	125

